



◀▶ SAFETY CHARACTERISTICS	0
◀▶ SIGNIFICANT CHARACTERISTICS	0
◀▶ CUSTOMER INTERFACE	2

Non è permesso copiare o riprodurre questo documento, né utilizzare il contenuto o renderlo comunque noto a terzi senza permesso scritto dalla WABCO. È vietata espressamente la ristampa o l'uso non autorizzato. Toute réimpression ou reproduction de son contenu sans autorisation écrite de la WABCO est formellement interdite. Toute utilisation non autorisée de ce document est formellement interdite. Wichtige sowie Verwechslungsdauer, Verwertung und Mitteilung hierin ist nicht gestattet, soweit nicht ausdrücklich anders angedeutet ist. Die Rechte für den Fall der Patentverletzung oder Gebrauchsmuster-Verletzung sind vorbehalten. All rights reserved for patent or registration of a utility model or design. This document is the subject of copyright.

1	MAX.REBOUNDE LENGTH
2	MIN.COMPRESSION LENGTH
3	MARKING DETAILS PROVIA LOGO PROVIA PART NUMBER DATE OF MANUFACTURING
4	HARDNESS OF RUBBER PARTS 66-73 HS
5	HARDNESS OF RUBBER PARTS 65-70 HS
6	WELD STRENGTH 45KN
7	WELD STRENGTH 35KN
	COLOUR: RAL 9005B SEMI-BLACK

Resistance force table of SAMPLE criterion - HYDRAULIC

V (m/s)	0.052	0.131	0.262	0.393	0.524
Rebound (N)	1495	1487/2479	2226	2458	2270/3072
Compression (N)	233	525/875	816	904	838/1135
S (mm)	100				

General Specifications: ISO 8015, JED-334-1, Size ISO 14405 LP		Copyright WABCO®	
Further Technical Data: PRO 600 018 0		Date	Signature
Doc. Code: O35	Sheet: 1 To 7	2023-01-15	Saravanan
General Tolerances JED-261		2023-01-17	
Range of Nominal Dimensions (± mm)		Manivannan	
Class	1)	≤ 50	> 50 ≤ 180
Fine		±0.5	±1 ±1.5 ±2
Medium	x	±1	±2 ±3 ±4 ±3°
Coarse		±2	±3.5 ±5 ±6.5
Tapped Holes acc. -		Dimensions in mm	
1) Tolerance Class Applied Crossmarked		Mass	Scale
		3.7 ± 1	1:1
		kg	
		Size	CAD System
		A 1	CREO
		Material No.	
		PRO 600 026 0	
		Date of first issue:	2023-01-17
		Doc.Code	Language
		005	EN
		Sheet	1/1
		Techn. Resp.	6961AM
		Replacement for	